

BRK Ghost upgrade spring fitting instructions



The kit includes.

The Hammer Spring Power Tuning Kit allows BRK Ghost shooters to fine-tune their rifle for shooting different pellets or slugs. This is a genuine BRK Brocock Performance Center upgrade.

Suitability

For all 'export' or Hi-Power (HP) models. The kit comprises six, color-coded springs of pre-set tensions, as fitted at the factory to the following configurations.

430mm barrels

WHITE – .177 / 4.5mm rated up to 12 ft/lbs

WHITE – .22 / 5.5mm rated up to 20 ft/lbs

BLUE – .177 / 4.5mm rated up to 20 ft/lbs

BLUE – .22 / 5.5mm rated up to 45 ft/lbs

600mm barrels

RED – .177 / 4.5mm rated up to 31 ft/lbs

RED – .22 / 5.5mm rated up to 61 ft/lbs

RED – .25 / 6.35mm rated up to 70 ft/lbs

BLACK – .30 / 7.62mm rated up to 95 ft/lbs

Special barrels

GREEN – .22 (711mm RACE edition)

YELLOW – HP+ models

To fit:

Ensure gun is unloaded and rifle is not cocked.

Remove 4x3mm securing screws. Note: this is anti-tamper on many UK spec models and 3mm on other regions. The lower screws can be accessed by lowering the butt pad.



Remove rear body assembly



Remove power wheel



Remove spring and replace with spring of a different rating



Replace power wheel not orientation of ball bearing that must match with the ball bearing groove

Replace rear housing